

## Contarnex Europe Limited

### LED Digital Clocks

### LUMEX 14-19-25

#### LUMEX – Digital Clocks for business environments

- Digits in three sizes, 140/190/250 mm height.
- Red diodes with light intensity for indoor environment. (300 mcd)
- Red diodes with light intensity for outdoor environment. (1000 mcd)
- Housing of aluminium. Outdoor version IP54.
- Light intensity adjustable by dimmer control.
- Automatic summer/winter time change.

#### Options

- Infrared remote control unit with operation range of approx 15 m.
- Green diodes (only indoor versions)
- Receiver for time synchronisation by DCF, RDS, GPS, MSF
- Minute impulse input for operation from master clock.
- Connection for IRIG-B.
- Connection for LIC (SMPTE/EBU).
- Connection for LON.

#### Legibility

- 140 mm digits approx 50 m
- 190 mm digits approx 65 m
- 250 mm digits approx 80 m

#### Technical datas

Connection to mains      230V AC  
Power reserve              48 hours  
Accuracy                    ± 1 sec/24 hours

EN50081 and EN50082 compliant.



#### Art No.

Digit height	Indoor/Outdoor	Single/Double	Art. No.
140	I	S	119750-00
140	I	D	119751-00
190	I	S	119752-00
190	I	D	119753-00
250	I	S	119754-00
250	I	D	119755-00
140	O	S	119760-00
140	O	D	119761-00
190	O	S	119762-00
190	O	D	119763-00
250	O	S	119764-00
250	O	D	119765-00

#### Dimensions and weight.

Digit height	Single/Double	Dimensions W/H/D mm	Weight Kgs
140	S	690/250/155	7.5
140	D	690/250/155	8.5
190	S	820/300/155	9.5
190	D	820/300/155	11
250	S	1020/370/155	12
250	D	1020/370/155	14