



09 Feb 2016

# 50cd Obstruction Light - 12Vdc

CEL-50-12-CST - LED Aircraft Warning Light

### Key features

- Based on LED technology
- 50cd luminuous output
- Steady burning red light
- Complete set with accessories
- Extremely reliable
- Very long life time
- Low power consumption
- 12VDC operating voltage
- Stabilised light output
- Easy to install
- Mounting set and terminal box included

#### **Benefits**

- Long maintenance intervals
- Low energy costs
- Input voltage variations do not effect light output
- Very low lifetime costs

#### **Optical characteristics**

- Intensity >50cd
- Colour aviation red
- Horizontal radiation pattern 360°
- Vertical radiation pattern 23°
- Current for the LEDs are stabilised by constant current generator
- Light output degradation less than 30% after 100,000hrs of operation

#### **Electrical characteristics**

- LEDs are in separate groups
- Nominal operating voltage 12VDC
- Power consumption <12W (<1A constant current)
- Operating volage range 11,5 to 16VDC
- Overvoltage protection

### Other

- Black anodised aluminium housing
- Galvanised mounting arm
- Acid proof U-bolts and hex nuts
- Uncoloured glass cover
- Degree of protection IP65
- Operating temperature range -55 to+55°C
- Height 300mm, diameter140mm

Order Code: CEL-50-12-CST

- Wind load@ 200kmlh <150N
- Total weight 3.0 kg
- 5 year warranty


Also available with 24VDC, 48VDC and 230 VAC operating voltages  $\,$ 

Made in EU

Page 1 of 2



CEL-50-12-CST



# **Mechanical dimensions**



T: +44 (0)20 8540 1034 F: +44 (0)20 8543 3058 E: info@contarnex.com

Contarnex Europe Limited 252 Martin Way, Morden, Surrey SM4 4AW United Kingdom







# 50cd Obstruction Light - 12Vdc

# CEL-50-12-CST - LED Aircraft Warning Light

#### Installation Instructions

CEL-50-12-CST is an obstacle light utilising LED technology. The cabling and installation principles are similar to those of conventional obstacle lights, the only exception being the correct polarity required by DC feed.

Terminal box includes screw terminals and overvoltage protectors.


The polarity is:

Blue -Black + Yellow-Green PE

All connection alternatives can be protected with a 6A or 10A fuse or with a circuit breaker (C curve).

## Installation specifications

- Cable gland for lamp: M20, 8-13mm cable
- Cable gland for IN and OUT: M25, 11-17mm cable
- Wire diameter: max. 6mm<sup>2</sup>



CEL-50-12-CST terminal box

