

03 Feb 2016

Power Supply Unit - 230VAC/12VDC, 5A Optimised for CEL Aircraft Warning lights

CEL-PS-230-12-05

Key features

- Extremely reliable long lifetime
- Optimised for CEL LED obstacle lights
- 230 or 115 VAC input voltage / 12 VDC output voltage
- Degree of protection IP67
- Die cast aluminium enclosure
- Easy to install
- No RF-radiations


Electrical characteristics

- Input voltage 230 or 115VAC
- Power consumption max 100VA
- Output voltage 13VDC typical
- Maximum output current 5A

Mechanical characteristics

- Yellow powder painted die cast aluminium body
- Degree of protection to IP67
- Operating temperature range -55°C... +55°C
- Height 348mm, width 205mm, depth 115mm
- Weight 4kg





T: +44 (0)20 8540 1034 F: +44 (0)20 8543 3058 E: info@contarnex.com

Contarnex Europe Limited 252 Martin Way, Morden, Surrey SM4 4AW United Kingdom



Order Codes:

CEL-PS-230-12-05 for 230 Vac system CEL-PS-230-12-05-PCFL for 230 Vac system with flasher CEL-PS-115-12-05 for 115 Vac system CEL-PS-115-12-05-PCFL for 115 Vac system with flasher

Made in EU

Page 1 of 1

www.contarnex.com